



PA472

VAN MEDEVOORT

STEREO POWER AMPLIFIER



Features:

- 250 Watt stereo music power
- Handles any loudspeaker system including ESL
- Very low distortion, dynamic class 'A' technology
- Highly musical performance
- XLR and RCA gold plated input connectors
- Protection circuitry and muting
- Remote controlled on / stand-by via DC bus
- Silver / black finished front plate

The Van Medevoort PA472 dual mono power amplifier is built with very fast, low-distortion, balanced dynamic class 'A' power stages and two more than generous power supply sections. This produces top quality musical performance and best control over your loudspeaker system for any type of music. The housing is extremely sturdy with the same nice silver / black finished front plate as the vM CA470. Only audiophile quality components are used. A 12 Volt DC input is provided to switch the vM PA472 on and stand-by with the remote control bus of your vM control amplifier.

Specifications:

Nominal power	> 2x 250 Watt / 8 Ohms
Damping factor	1200 - 1500
Input impedance	100 kOhms
Input level	1.5 V _{eff.} / 250 Watt
Distortion	< 0.003 % / 1 - 100,000 Hz
Signal to noise ratio	> 104 dB
Inputs / connectors	2 / XLR + RCA switchable
Outputs / connectors	2 / 5 way binding posts
Power supply	115-230 Volt / 50-60 Hz
Power consumption	5/60-500 Watt stb/min-max
Weight	17,5 kg
Size w x h (h+feet) x d	434 x 88 (102) x 410 mm

Options: vM Silver Cable

Van Medevoort
Audio products

Visit our website for more information.
Copyright © 2015 Van Medevoort Audio / The Netherlands.
Specifications are subject to change without prior notice.

www.vanmedevoortaudio.nl
contact@vanmedevoortaudio.nl